



**Rough Opening**  
**10.82" wide x 5.31" high**  
**(275 x 135mm)**  
**3.34" (85mm) minimum**  
**recessed depth**

### Material:

- **Shell and Flanges** : 18-8, Type-304, 22-gauge (0.8mm) stainless steel. One-piece, seamless construction with four countersunk mounting holes.
- **Support Posts** : Four Heavy-duty cast zamak support posts with chrome-polished finish.
- **Mounting Bracket(2)** : Plated steel mounting clamp attaches to back of unit with four sheet-metal screws for installation in stud wall construction and countertop aprons.
- **Spindles(2)** : Four Chrome-polished plastic spindles equipped with heavy-duty internal springs.
- **Hood(2)** : 18-8 Type-304, 22-gauge (0.8mm) stainless steel. Hood hinged to shell.

### Installation:

- For installation in stud wall construction and countertop aprons without backing, Loosely attach the mounting clamp to back of the unit with sheet-metal mounting screws.
- Insert the product into the rough opening. Adjust mounting clamp so it grips surface inside rough opening.
- Secure in place by tightening two sheet-metal mounting screws.

**Note:** For installation in stud wall construction and countertop aprons with backing: Discard mounting clamp furnished with unit. Insert the unit only into a rough opening and secure with sheet-metal screws furnished. Backing must comply with local building codes

### Specification:

- Recessed toilet tissue dispenser shall be constructed of Type-304, 22-gauge (0.8mm) stainless steel with Chrome polished finish. Shell and flange shall be drawn, one-piece, seamless construction. The Spindle shall be equipped with a heavy-duty internal spring. Unit shall be furnished with plated steel mounting clamp for stud wall construction and countertop aprons.